



Printing date 05/08/2015

Reviewed on 05/08/2015

1: Identification

- · 1.1 Product identifier
- · Trade name: D-100 Developer Spray Can
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

NDT Inspection developer "form d & e" per AMS-2644/ASTM E-1417

- 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Sherwin Incorporated 5530 Borwick Ave South Gate, CA 90280 Phone: (562) 861-6324 Fax: (562) 923-8370 https://www.sherwininc.com/

- · Information department: Product safety department
- · 1.4 Emergency telephone number:

Chemtrec +1-800-424-9300 in U.S.A.; outside U.S.A. 001-703-527-3887

Chemtrec contract number 20103

2: Hazard(s) identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapor.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Flammable Aerosol 1 H220

Gases Under Pressure - Compressed Gas

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labeled according to the CLP regulation.

· Hazard pictograms





GHS02

02 GHS07

- · Signal word Danger
- $\cdot \ \textbf{Hazard-determining components of labeling:}$

propan-2-ol (isopropyl alcohol)

Propane

Butane

Hazard statements

H220 Flammable aerosol. Contains gas under ressure; may explode if heated.

H225 Highly flammable liquid and vapor.

H319 Causes serious eve irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking

P233 Keep container tightly closed.

P240+P241 Use explosion-proof electrical/ventilating/lighting/equipment. Ground container.

P261+P271 Avoid breathing product. Use in a well ventilated area.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower.

(Contd. on page 2)





Printing date 05/08/2015 Reviewed on 05/08/2015

Trade name: D-100 Developer Spray Can

(Contd. of page 1)

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, ifpresent and easy to do. Continue rinsing. If eye irritation persists: Get

medical attention.

P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a

position comfortable for breathing. Call a POISON CENTER or

doctor/ physician if you feel unwell.

P233+P405 Keep container tightly closed. Store locked up.

P403+P410 Protect from sunlight. Store in a well-ventilated place. Do not expose to

temperatures exceeding 50 °C/122 °F

P501 Dispose of contents/container in accordance with local/regional/national/international

· Classification system:

· NFPA ratings (scale 0 - 4)

· HMIS-ratings (scale 0 - 4)



Health = 2 Fire = 4 Reactivity = 0



Health =2
Fire = 4
Reactivity = 0

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3: Composition/information on ingredients

- · 3.2 Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 67-63-0 EINECS: 200-661-7	propan-2-ol	50-60%
CAS 74-98-6	Propane	1-10%
CAS 75-28-5	Butane	1-10%

4: First-aid measures

- · 4.1 Description of first aid measures
- · After inhalation:

Supply fresh air. If required, provide artificial respiration.. Consult doctor if you feel unwell. In case of unconsciousness place patient stably in side position for transportation and call doctor.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly. Take off contaminated clothing. If skin irritation continues, consult a doctor.

· After eye contact:

Immediately rinse opened eye for 15I minutes under running water. Remove contact lens. If symptoms persist, consult a doctor.

· After swallowing:

Rinse mouth. Do not induce vomiting. Keep respiratory tract clear. If symptoms persist, immediately call for medical help. A person vomiting while lying on their back should be turned onto their side.

(Contd. on page 3)





Printing date 05/08/2015 Reviewed on 05/08/2015

Trade name: D-100 Developer SPRAY CAN

(Contd. of page 2)

 \cdot 4.2 Most important symptoms and effects, both acute and delayed

May cause drowsiness, dizziness, headaches, severe eye irritation.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5: Fire-fighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, sand, extinguishing powder. Do not use water.

Foam

ABC powder

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture Spray cans are under pressure. Carbon monoxide and carbon dioxide
- · 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device, if necessary. Wear fully protective suit.

6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Spray cans are under pressure Wear protective equipment. Keep unprotected persons away. Eliminate ignition sources. Ensure adequate ventilation. Avoid breathing mist or vapors.

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Collect liquid in an appropriate container or absorb with an inert material such as vermiculite, dry sand, or earth; DO NOT use combustible materials.

Place in a chemical waste container.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7: Handling and storage

- 7.1 Precautions for safe handling Prevent breathing of mists or vapors. Practice good hygiene..
- · Information about protection against explosions and fires:

Keep away from sources of ignition. - No smoking. Do not spray on an open flame or other Ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid contact Avoid with skin and eyes. Avoid breathing vapor or mist. Do not swallow.

Use only outdoors or in a well-ventilated area. When using do not eat, drink or smoke. (See section 8)

Containers may be hazardous when empty since residue may be present 7.2

Conditions for safe storage, including any incompatibilities

· Storage:

No smoking.

Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 $^{\circ}$ C/122 $^{\circ}$ F

· Requirements to be met by storerooms and receptacles: Store in a cool location.

(Contd. on page 4)





Printing date 05/08/2015 Reviewed on 05/08/2015

Trade name: D-100 Developer SPRAY CAN

(Contd. of page 3)

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· 7.3 Specific end use(s) No further relevant information available.

8: Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · 8.1 Control parameters
- · Components with limit values that require monitoring at the workplace:

67-63-0 propan-2-ol OSHA PEL: 980 mg/m³, 400 ppm

ACGIH STEL: 400 ppm TWA 200 ppm

NIOSH STEL: 1225 mg/m³, 500 ppm TWA: 980 mg/m³, 400 ppm

Propane, isobutane OSHA PEL TWA 1000 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:



Ventilation System: A system of local or general exhaust is recommended to keep employee exposure below the airborne exposure limits. If exposure limit is exceeded use organic vapor respirator (type A), or self contained breathing apparatus.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)





Printing date 05/08/2015 Reviewed on 05/08/2015

Trade name: D-100 Developer SPRAY CAN

(Contd. of page 4)

Eye protection:



Safety glasses

Tightly sealed goggles

• Body protection: Use protective suit. Choose body protection according to the amount and concentration of the dangerous substance at the work place.

9.1 Information on basic physical ar	nd chemical properties
General Information	
Appearance:	Onner and an analysis White limited are a small and
Form: Color:	Spray can under pressure. White liquid, gas propellant White
Odor:	Charactertistic
Odour threshold:	Not determined.
pH-value:	Not applicable.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Isopropyl alcohol portion: 82 °C (180 °F)
Flash point, solvent:	Isopropyl alcohol portion: 12 °C (53.6 °F)
gnition temperature:	Isopropyl alcohol portion: 425 °C (797 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not self igniting.
Danger of explosion:	Can under pressure with a flammable gas.
Explosion limits:	Isopropyl alcohol portion:
Lower:	2.0 Vol %
Upper:	13.0 Vol % Propellant: 9.5% (vol.) Gas in air
Vapor pressure at 20 °C (68 °F):	No data available
Density at 20 °C (68 °F):	Isopropyl alcohol portion: 0.859 g/cm3 (7.2 lbs/gal)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Powder not soluble
Partition coefficient (n-octanol/wate	r): Not determined.
Viscosity:	
Dynamic:	Not determined.



Printing date 05/08/2015 Reviewed on 05/08/2015

Trade name: D-100 Developer SPRAY CAN

(Contd. of page 5)

• 9.2 Other information

No further relevant information available.

10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials:

Avoid contact with bases, acids, and oxidizing agents

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity: Information on hazardous ingredients
- · LD/LC50 values that are relevant for classification:

67-63-0 propan-2-ol

Acute oral toxicity	LD50	5.03 g/kg (rabbit)
Acute inhalation toxicity:	LC50/4h	>20 mg/kg (rat)
Acute dermal toxicity:	LD50	12800 mg/kg (rabbit)

- · Primary irritant effect:
- · on the skin: Mild
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

No component of this product is identified as probable, possible or confirmed human carcinogen

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

USA





Printing date 05/08/2015 Reviewed on 05/08/2015

Trade name: D-100 Developer SPRAY CAN

(Contd. of page 6)

12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

Information on hazardous ingredients

67-63-0 propan-2-ol				
Toxicity, fish	LC50/96h : >100 mg/l			
Toxicity	EC50/48hr (Daphnia magna): >100 mg/l			

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Waste/ unused products

Collect all waste in suitable and labeled containers and dispose according to local legislation.

- · Uncleaned packagings:
- · Recommendation:

Depressurize can

Waste / used products

Waste products and empty packages dispose of in accordance with local regulations.

Empty containers may contain flammable residue and vapors.

14: Transport information

· 14.1 UN-Number

DOT

ADR, IMDG, IATA

Consumer commodity ORM-D

UN1950

14.2 UN proper shipping name

· DOT

· ADR· IMDG, IATA

Consumer commodity ORM-D

Aerosols, flammable

(Contd. on page 8)

US





Printing date 05/08/2015 Reviewed on 05/08/2015

Trade name: D-100 Developer SPRAY CAN (Contd. of page 7) · 14.3 Transport hazard class(es) \cdot **DOT** Class Not applicable · Label ORM-D · ADR, IMDG, IATA · Class Aerosols, flammable, 2.1 · Label Flammable gas, 2.1 · 14.4 Packing group Not applicable \cdot DOT ADR, IMDG, IATA None · 14.5 Environmental hazards: · Marine pollutant: Not applicable · 14.6 Special precautions for user Warning: Flammable gas · Transport/Additional information: \cdot DOT · Quantity limitations On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg

Page 9





Safety Data Sheet acc. to OSHA HCS

Printing date 05/08/2015 Reviewed on 05/08/2015

Trade name: D-100 Developer SPRAY CAN

(Contd. of page 8

15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

67-63-0 propan-2-ol

Section 311/312

Fire hazard Acute health hazard

· TSCA (Toxic Substances Control Act):

All components listed

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

- · Carcingenity categories
- EPA (Environmental Protection Agency)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Contact: Sherwin Incorporated
- · Date of preparation / last revision 05/08/2015 / -
- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, ÉU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3