



Penetrant Professor Approved



Met-L-Chek Company manufactures a complete line of penetrants used in the fluorescent (Type 1) and visible (Type 2) dye penetrant inspection process. All Met-L-Chek Company penetrants are qualified to AMS-2644 and are sold under the Met-L-Chek® and Pen-Chek® trademarks. Met-L-Chek Company products are manufactured under license in The Netherlands by NDT Europa.

FP-922 is approved to AMS-2644 as a fluorescent (Type 1); Methods “A”, and “C”; sensitivity level 2 water washable inspection penetrant. For Method “C” applications it is used with E-59, E-59A, R-503, and R-504.

FP-922 is applied by immersion, spray, or wipe on. It is approved for medium sensitivity aerospace applications.

FP-922 is listed on the Qualified Products List for AMS-2644. It meets the requirements of AMS-2647, ASME Boiler and Pressure Vessel Code Section V, ASTM E-165, and ASTM E-1417, for penetrant inspection materials. It is low in sulfur and halogens and is safe for use on all metal surfaces.

Guide to METHOD “A” processing per  
ASTM E-1417

Guide to METHOD “C” (wipe off) processing per  
ASTM E-1417

1. Part must be clean, dry and at a temperature of 4.4°-52°C (40°- 125°F) before penetrant is applied.
2. Apply FP-922 penetrant using spray, immersion, or wipe on.
3. Wait a minimum of 10 minutes; 20 minutes if temperature is 4.4°-10°C (40-50°F).
4. Wash part; water temperature 10°-38°C (50°-100 °F). Water pressure < 275kPa (< 40 psi); if a hydro-air nozzle is used, limit pressure to < 172kPa (< 25 psi). Distance > 30cm (> 12 inches). Wash time- only long enough to remove surface fluorescence under UV-A (black light) .
- 5\*. Dry part; temperature not to exceed 71°C (160°F), time - only long enough to dry surface.
6. Apply dry powder developer, form “a” (D-72A), by dusting, or non aqueous developer, form “d”(D-70), by spraying.
- 6A\*. If water based developer form “c”(D-78B) is used it is applied by immersion or spray, prior to step 5 drying.
7. Wait a minimum of 10 minutes before inspection. Maximum time is 1 hour for form “d ” (non aqueous) and maximum 4 hours for form “a” (dry powder). If times are exceeded, clean part and reprocess.
8. Use UV-A illumination of >1000 μW/cm<sup>2</sup> @ 15 inches (38.1 cm) in a darkened area of < 21 lux visible light (< 2 foot candles).

1. Part must be clean, dry and at a temperature of 4.4°-52°C (40°- 125°F) before penetrant is applied.
2. Apply FP-922 penetrant using spray, immersion, or wipe on.
3. Wait a minimum of 10 minutes; 20 minutes if temperature is 4.4°-10°C (40-50°F).
4. Moisten cloth with E-59, E-59A, R-503 or R-504 and wipe penetrant from surface. Do not spray remover on surface to remove penetrant, as sensitivity will be impaired. Water may be used to wipe FP-922 from the surface, but the surface must be dried before developer is applied.
5. Apply dry powder developer D-72A by dusting, or non aqueous developer D-70 by spraying.
6. Wait a minimum of 10 minutes before inspection.
7. Inspect under UV-A illumination of >1000 μW/cm<sup>2</sup> @ 15 inches (38.1 cm) in a darkened area of < 21 lux visible light (< 2 footcandles).

Fluorescent Penetrant Indication





Penetrant Professor Approved

# FP-922

## Fluorescent Penetrant

### Typical Physical Properties

Form: clear yellow green liquid  
 Density: 902 g/L  
 Flash Point: > 93°C (> 200°F)  
 Viscosity 8.7 mm<sup>2</sup>/s  
 Water Tolerance:> 9 %  
 Water Content: < 1 %  
 Fluorescent Brightness: (AMS-2644 requirement > 80 %) 109.8%  
 Corrosion of aluminum: none  
 Corrosion of carbon steel: none  
 Corrosion of magnesium: none  
 Corrosion of stainless steel: none  
 Corrosion of titanium: none  
 Chloride content: < 100 ppm (0.01%)  
 Fluoride content: < 50 ppm (0.005%)  
 Sodium content: < 100 ppm (0.01%)  
 Sulfur content: < 100 ppm (0.01%)  
 Mercury: none  
 VOC's: 0 g/L  
 Ozone layer depleting substances: none  
 PCB's: none

The warranty shelf life of the product is 5 years from date of batch approval.

### Specifications

<b>AMS-2644</b>	<b>AMS-2647</b>
<b>ASME B &amp; PV code Sec. V</b>	
<b>ASTM E-165</b>	<b>ASTM E-1417</b>
<b>ISO-3452</b>	<b>P &amp; W PMC # 4351-7</b>
<b>SPOP-82</b>	<b>R-R RPS-702</b>
<b>R-R CSS-232</b>	<b>Snecma sensibilité S2</b>

### Product Availability

1 pint (0.4L) can with dauber  
 1 gallon (3.7L) can  
 5 gallon (18.9L) pail  
 55 gallon (208L) drum

**NSN #**

1 gallon	6850-01-267-7987
5 gallon	6850-01-263-2261
55 gallon	6850-01-263-2262



### GHS Information



#### Danger

**GHS Hazard Statements:**  
**H315** Causes skin irritation.  
**H318** Causes serious eye damage.

#### GHS Precautionary statements:

**P102:** Keep out of reach of children.  
**P210:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
**P261:** Avoid breathing fumes/gas/mist/vapors/spray.  
**P273:** Avoid release to the environment.  
**P280:** Wear protective glove/clothing/eye protection/face protection.  
**P284:** In case of inadequate ventilation wear respiratory protection.



#### GHS response statements:

**IF INHALED:** Remove person to fresh air and keep comfortable for breathing, get medical advice/attention if you feel unwell.  
**IF ON SKIN:** Wash with plenty of water. If skin irritation occurs, get medical advice/attention.  
**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easily to do. Continue rinsing, get medical attention.  
**IF SWALLOWED:** Immediately call a poison center/doctor/physician. Do Not induce vomiting.  
**IF ON CLOTHING:** Take off contaminated clothing and wash it before reuse.

#### Transport:

DOT- not regulated < 450 L or 119 Gal containers  
 IATA- not regulated  
 IMDG- not regulated

Met-L-Chek Company, 1639 Euclid Street, Santa Monica, California, 90404, U.S.A.

Phone: 310-450-1111, Fax: 310-452-4046, Email: info@met-l-chek.com, Web: www.met-l-chek.com